









4xAA 1.5V

2.8 kg 0.350 kg

L 39 x W 31 x H 11 cm



Article code:

Material: Cleaning instructions:

Cartridge: Flow ^{at water of 38°C}: Pressure: Sensor (de)activation time: 700-1530 Brushed 700-1532 Hammercoated black

Stainless Steel r304 download JEE-O shower and taps manual on our website: www.jee-o.com sedal ired+ electronic infrared operated valve 10L p/m at 3Bar pressure Recommended working pressure 3Bar <1s Connection: Thread: Power supply:

Power consumption:

Battery type (optional): Dimension package: Total weight: Package weight:

Protection against intrusion: valve IP65 and sensor IP67 7 year warranty steel parts and 1 year on electronics The general terms and conditions can be found on our website: www.jee-o.com/downloads

HS Code: Approvals: 8481801190 WRAS, ACS (XP P41-280)

G ½-14 British Standard Pipe (BSP) DC 6V; AC 230 V (50Hz)/ 110-120V (60Hz) standby: AC < 4W ; DC < 0.2mW flushing: AC < 5W ; DC < 3W

JEE-O soho touchless wall basin tap specifications | September 2023

Models are subject to change and specs may contain typographical errors Slight variations in the aesthetic appearance of the product, including the color, may occur after exposure to external influences such as sunlight, pollution or harmful chemicals